Convection Oven

Electric Convection Oven, 10 GN1/1



240454 (ZFCE11CSDS)
Convection oven crosswise, 10x1/1GN, electric

240455 (ZFCE11CSCS)
Convection oven crosswise, 10x1/1GN, electric

Main Features

- Drip tray to collect residual cooking juices and fat.
- Maximum temperature of 300°C.
- Food temperature probe (available as accessory).
- Rapid cooling of oven cavity.
- Halogen lighting and “crosswise” pan supports allow clear and unobstructed view of the products being cooked.
- Main switch/Cooking mode selector which can be used to set: ON/OFF, hot air without humidification and hot air with humidification (choice of 5 different humidity levels).
- Timer to set the cooking time, adjustable up to 120 minutes or for continuous operation with an acoustic alarm to show the cycle has finished. At the end of the set cooking time the heat and the fan are automatically switched off.
- Perfect evenness: guarantees perfect distribution of heat throughout the oven cavity.
- Capacity: 10 GN 1/1 trays.
- Drip tray under the door to collect condensed liquid available as accessory.
- Manual valve to adjust the position of steam evacuation flap.

Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- IPx4 water protection.
- Integrated drain outlet.
- 1 pair of 60 mm pitch runners is supplied as standard.
- Robust structure thanks to stainless steel construction.
- Ergonomic door handle.
- Cooking chamber in 430 AISI stainless steel.

Included Accessories

PNC Code	Description	Quantity
922121	60mm pitch side hangers for 10 1/1 GN electric oven	1

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Optional Accessories

PNC Code	Description
Bases & base accessories	
922102	Open base for 10 GN 1/1 convection oven
922106	Shelf guides for 10 1/1 GN oven base
922114	Open base on castors for 10 GN 1/1 convection oven
Containers, trays and grids	
921101	Pair of AISI 304 stainless steel grids, GN 1/1
922017	Pair of AISI 304 stainless steel grids, GN 1/1
922036	Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1
922062	AISI 304 stainless steel grid, GN 1/1
922239	Pair of frying baskets
922266	Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1
922325	Kit universal skewer rack and 6 short skewers for Lengthwise GN 2/1 and Crosswise ovens
922713	Mesh grilling grid, GN 1/1
925000	Non-stick universal pan, GN 1/1, H=20mm
925001	Non-stick universal pan, GN 1/ 1, H=40mm
925002	Non-stick universal pan, GN 1/1, H=60mm
925003	Double-face griddle, one side ribbed and one side smooth, GN 1/1
925004	Aluminum grill, GN 1/1
925005	Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1
Feet, wheels and ramps	
922127	Feet for convection ovens 10 GN1/1 & 10 GN2/1
Food probes	
921702	Probe for 6-10 1/1 GN ovens
Grease/oil management	
922178	Fat filter for 10 1/1 and 2/1 GN combi steamers (gas and electric) and convection ovens (electric)
Handling - gastronorm	
921713	1/1 GN drain pan guide kit
922115	80mm pitch side hangers for 10 1/1 GN electric oven
922121	60mm pitch side hangers for 10 1/1 GN electric oven
Other accessories	
922338	Smoker for lengthwise and crosswise oven
Spray units	
922170	Retractable hose reel water spray unit
922171	External side spray unit (needs to be mounted outside and includes support to be mounted on the oven)
Other accessories	
921106	Support for 1/2GN pan (2pcs)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Recommended Detergents


PNC Code	Description
0S2282	EXTRA STRONG DETERGENT FOR OVEN C20-2pzx5L
0S2283	EXTRA STRONG RINSE AID C21-2pzx5L

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.


Technical specifications

	240454	240455
Electric		
Supply voltage:	380-400 V/3N ph/50 Hz	230 V/3 ph/50 Hz
Auxiliary:	0.3 kW	0.3 kW
Capacity:		
Trays type:	10 - GN 1/1	10 - GN 1/1
Shelf capacity:	10 Grids	10 Grids
Key Information:		
External dimensions, Width:	890 mm	890 mm
External dimensions, Depth:	900 mm	900 mm
External dimensions, Height:	970 mm	970 mm
Net weight:	121.2 kg	121.2 kg
Functional level:	Basic	Basic
Runners pitch:	60 mm	60 mm
Cooking cycles - air-convection:	300 °C	300 °C
Internal dimensions, Width:	590 mm	590 mm
Internal dimensions, Depth:	503 mm	503 mm
Internal dimensions, Height:	680 mm	680 mm


Front



Side



Top



CWI1 = Cold Water inlet 1 (cleaning)
D = Drain
EI = Electrical inlet (power)
DO = Overflow drain pipe